

WHAT IS CLAIMED IS:

1. A developer carrier for carrying a developer, the developer carrier comprising:

an opposing region that opposes a latent image-

5 carryable region on an image carrier, and

a solid portion that is solid at an end portion of the developer carrier in a longitudinal direction thereof;

wherein an end of the solid portion, which is on a side of a center of the developer carrier in the longitudinal direction, is located closer to the center of the developer carrier than an edge of the opposing region.

2. The developer carrier according to claim 1, wherein the developer carrier is formed by fitting a solid axial member into an end portion of a hollow roller in the longitudinal direction.

3. The developer carrier according to claim 1, wherein the developer carrier is manufactured by conducting at least one of cutting and polishing.

4. A developing device comprising:

a developer carrier for carrying a developer, including

an opposing region that opposes a latent image-

25 carryable region on an image carrier, and

a solid portion that is solid at an end portion of the developer carrier in a longitudinal direction thereof,

wherein the developing device develops a latent image carried in the latent image-carryable region with the

5 developer carried on the developer carrier, and

an end of the solid portion, which is on a side of a center of the developer carrier in the longitudinal direction, is located closer to the center of the developer carrier than an edge of the opposing region.

10

5. The developing device according to claim 4, wherein the developer carrier is formed by fitting a solid axial member into an end portion of a hollow roller in the longitudinal direction.

15

6. The developing device according to claim 4, wherein the developer carrier is manufactured by conducting at least one of cutting and polishing.

20

7. The developing device according to claim 4, further comprising an abutment member that abuts against the developer carrier along the longitudinal direction of the developer carrier,

wherein the developer carrier is supported at both ends
25 in the longitudinal direction thereof so that the developer

carrier is abutted with the abutment member along the longitudinal direction of the developer carrier.

8. The developing device according to claim 7, wherein the
5 abutment member presses the developer carrier towards the image carrier.

9. The developing device according to claim 7, wherein the
abutment member is a developer supply member for supplying
10 the developer to the developer carrier.

10. The developing device according to claim 7, wherein the
abutment member is a layer thickness regulating member for
regulating a layer thickness of the developer carried on the
15 developer carrier.

11. The developing device according to claim 4, wherein the
developer carrier is made of metal.

20 12. The developing device according to claim 4, wherein the
developing device develops the latent image carried in the
latent image-carryable region in a state that the developer
carrier and the image carrier are not in contact with each
other.

13. A developing device comprising:

a developer carrier for carrying a developer, including
an opposing region that opposes a latent image-
carryable region on an image carrier, and

5 a solid portion that is solid at an end portion of
the developer carrier in a longitudinal direction thereof,

wherein the developing device develops a latent image
carried in the latent image-carryable region with the
developer carried on the developer carrier, and

10 an end of the solid portion, which is on a side of a
center of the developer carrier in the longitudinal
direction, is located closer to the center of the developer
carrier than an edge of the opposing region,

wherein the developer carrier is formed by fitting a
15 solid axial member into an end portion of a hollow roller in
the longitudinal direction,

wherein the developer carrier is manufactured by
conducting at least one of cutting and polishing,

wherein the developing device further comprises an
20 abutment member that abuts against the developer carrier
along the longitudinal direction of the developer carrier,
and

the developer carrier is supported at both ends in the
longitudinal direction thereof so that the developer carrier
25 is abutted with the abutment member along the longitudinal

direction of the developer carrier,

wherein the abutment member presses the developer carrier towards the image carrier,

wherein the abutment member is a developer supply

5 member for supplying the developer to the developer carrier

wherein the developer carrier is made of metal,

wherein the developing device develops the latent image carried in the latent image-carryable region in a state that the developer carrier and the image carrier are not in

10 contact with each other.

14. An image forming apparatus comprising a developing device including:

an image carrier for carrying a latent image, and

15 a developer carrier for carrying a developer, the developer carrier including an opposing region that opposes a latent image-carryable region on the image carrier and a solid portion that is solid at an end portion of the developer carrier in a longitudinal direction thereof,

20 wherein the developing device develops a latent image carried in the latent image-carryable region with the developer carried on the developer carrier, and

an end of the solid portion, which is on a side of a center of the developer carrier in the longitudinal

25 direction, is located closer to the center of the developer

carrier than an edge of the opposing region.

15. A computer system comprising:

a computer mainframe;

5 a display device connectable to the computer mainframe
and

an image forming apparatus connectable to the computer
mainframe, the image forming apparatus comprising a
developing device including:

10 an image carrier for carrying a latent image, and
a developer carrier for carrying a developer, the
developer carrier including an opposing region that opposes
a latent image-carryable region on the image carrier and a
solid portion that is solid at an end portion of the
15 developer carrier in a longitudinal direction thereof,

wherein the developing device develops a latent image
carried in the latent image-carryable region with the
developer carried on the developer carrier, and

an end of the solid portion, which is on a side of a
20 center of the developer carrier in the longitudinal
direction, is located closer to the center of the developer
carrier than an edge of the opposing region.

16. A developing device comprising:

25 a developer carrier for carrying a developer,

wherein the developing device develops a latent image carried on an image carrier with the developer carried on the developer carrier, in a state that the developer carrier and the image carrier are not in contact with each other,

5 and

a deflection amount of the developer carrier at an end portion of the developer carrier in a longitudinal direction thereof is smaller than a deflection amount at a center of the developer carrier in the longitudinal direction.

10

17. The developing device according to claim 16, further comprising an abutment member that abuts against the developer carrier along the longitudinal direction of the developer carrier,

15

wherein the developer carrier is supported at both ends in the longitudinal direction thereof so that the developer carrier is abutted with the abutment member along the longitudinal direction of the developer carrier.

20

18. The developing device according to claim 17, wherein the abutment member presses the developer carrier towards the image carrier.

19. The developing device according to claim 17, wherein

25

the abutment member is a developer supply member for

supplying the developer to the developer carrier.

20. The developing device according to claim 17, wherein
the abutment member is a layer thickness regulating member
5 for regulating a layer thickness of the developer carried on
the developer carrier.

21. The developing device according to claim 16, wherein
the developer carrier is made of metal.

10

22. The developing device according to claim 16, wherein
the latent image carried on the image carrier is developed
with the developer using a jumping development format.

15 23. A developing device comprising:

a developer carrier for carrying a developer, wherein
the developing device develops a latent image carried on an
image carrier with the developer carried on the developer
carrier in a state that the developer carrier and the image
20 carrier are not in contact with each other, and

a deflection amount of the developer carrier at an end
portion of the developer carrier in a longitudinal direction
thereof is smaller than a deflection amount at a center of
the developing carrier in the longitudinal direction,

25 wherein the developing device further includes an

abutment member that abuts against the developer carrier along the longitudinal direction of the developer carrier, and

the developer carrier is supported at both ends in the longitudinal direction thereof so that the developer carrier is abutted with the abutment member along the longitudinal direction of the developer carrier,

wherein the abutment member presses the developer carrier towards the image carrier,

wherein the abutment member is a developer supply member for supplying the developer to the developer carrier,

wherein the developer carrier is made of metal, and

wherein the latent image carried on the image carrier is developed with the developer using a jumping development format.

24. A developer carrier that carries a developer for developing a latent image carried on an image carrier in a state that the developer carrier and the image carrier are not in contact with each other,

wherein the deflection amount of the developer carrier at an end portion of the developer carrier in a longitudinal direction thereof is smaller than a deflection amount at a center of the developing carrier in the longitudinal direction.

25. An image forming apparatus comprising a developing device including:

an image carrier for carrying a latent image, and

5 a developer carrier for carrying a developer,

wherein the developing device develops a latent image carried on the image carrier with the developer carried on the developer carrier in a state that the developer carrier and the image carrier are not in contact with each other,

10 and

a deflection amount of the developer carrier at an end portion of the developer carrier in a longitudinal direction thereof is smaller than a deflection amount at a center of the developer carrier in the longitudinal direction.

15

26. A computer system comprising:

a computer mainframe;

a display device connectable to the computer mainframe;

and

20 an image forming apparatus connectable to the computer mainframe, the image forming apparatus comprising a developing device including

an image carrier for carrying a latent image, and

a developer carrier for carrying a developer,

25 wherein the developing device develops a latent image

carried on the image carrier with the developer carried on the developer carrier in a state that the developer carrier and the image carrier are not in contact with each other, and

5 a deflection amount of the developer carrier at an end portion of the developer carrier in a longitudinal direction thereof is smaller than a deflection amount at a center of the developer carrier in the longitudinal direction.

10 27. A developer charging unit comprising:

 a developer charging member for charging a developer carried on a developer carrier; and

 a support member for supporting the developer charging member, the support member being fixed with the developer
15 charging member by spot welding,

 wherein the support member includes a first bent portion and a second bent portion that are formed by bending a rectangular member along a longitudinal direction thereof,

 the support portion supports the developer charging
20 member and

 a direction in which the first bent portion is bent is opposite to a direction in which the second bent portion is bent, and

 the developer charging unit includes a free length
25 determining member for determining a free length of the

developer charging member.

28. The developer charging unit according to claim 27,
wherein the free length determining member includes an
5 abutment portion for abutting against the developer charging
member, and a distance from an end of the abutment portion
closest to a free length end of the developer charging
member to the free length end is shorter than a distance
from a fixed portion, at which the developer charging member
10 and the support member are fixed, to the free length end.

29. The developer charging unit according to claim 28,
wherein the developer charging member is nipped between the
free length determining member and the support member.

15

30. The developer charging unit according to claim 29,
wherein the developer charging member includes an elastic
body that abuts against a surface of the developer carrier
and an elastic body support member for supporting the
20 elastic body, and

the elastic body support member is nipped between the
free length determining member and the support member.

31. The developer charging unit according to claim 30,
25 wherein a thickness of the elastic body support member is 1

mm or less.

32. The developer charging unit according to claim 28,
wherein the abutment portion and the developer charging
5 member are fixed by spot welding.

33. The developer charging unit according to claim 27,
wherein the developer charging member and the support
portion are fixed by spot welding at plural places along a
10 longitudinal direction of the developer charging member.

34. The developer charging unit according to claim 27,
wherein the support member is fixed by screws to the free
length determining member at both end portions of the
15 support member in a longitudinal direction thereof.

35. The developer charging unit according to claim 27,
wherein the spot welding is laser welding.

20 36. A developer charging unit comprising:
a developer charging member for charging a developer
carried on a developer carrier; and
a support member for supporting the developer charging
member, the support member being fixed with the developer
25 charging member by spot welding,

wherein the support member includes a first bent portion and a second bent portion that are formed by bending a rectangular member along a longitudinal direction thereof, the support portion supports the developer charging

5 member and

a direction in which the first bent portion is bent is opposite to a direction in which the second bent portion is bent, and

the developer charging unit includes a free length
10 determining member for determining a free length of the developer charging member,

wherein the free length determining member includes an abutment portion for abutting against the developer charging member, and a distance from an end of the abutment portion
15 closest to a free length end of the developer charging member to the free length end is shorter than a distance from a fixed portion, at which the developer charging member and the support member are fixed, to the free length end,

wherein the developer charging member includes an
20 elastic body that abuts against a surface of the developer carrier and an elastic body support member for supporting the elastic body, and the elastic body support member is nipped between the free length determining member and the support member,

25 wherein a thickness of the elastic body support member

is 1 mm or less,

wherein the developer charging member and the support portion are fixed by spot welding at plural places along a longitudinal direction of the developer charging member,

5 wherein the support member is fixed by screws to the free length determining member at both end portions of the support member in a longitudinal direction thereof, and the spot welding is laser welding.

10 37. A developing device including

a developer carrier for carrying a developer, and

a developer charging unit including a developer charging member for charging the developer carried on the developer carrier and a support member for supporting the
15 developer charging member,

wherein the developer charging member and the support member are fixed by spot welding, and

the developing device develops a latent image carried on an image carrier with the developer carried on the
20 developer carrier,

wherein the support member includes a first bent portion and a second bent portion that are formed by bending a rectangular member along a longitudinal direction thereof,

the support portion supports the developer charging
25 member and a direction in which the first bent portion is

bent is opposite to a direction in which the second bent portion is bent, and

the developer charging unit includes a free length determining member for determining a free length of the developer charging member.

38. An image forming apparatus including
an image carrier for carrying a latent image,
a developer carrier for carrying a developer, and
10 a developer charging unit including a developer charging member for charging the developer carried on the developer carrier and a support member for supporting the developer charging member,

wherein the developer charging member and the support member are fixed by spot welding, and

the image forming apparatus develops the latent image carried on the image carrier with the developer carried on the developer carrier,

wherein the support member includes a first bent portion and a second bent portion that are formed by bending a rectangular member along a longitudinal direction thereof,
the support portion supports the developer charging member,

a direction in which the first bent portion is bent is
25 opposite to a direction in which the second bent portion is

bent, and

the developer charging unit includes a free length determining member for determining a free length of the developer charging member.

5

39. A computer system comprising:

a computer mainframe;

a display device connectable to the computer mainframe;

and

10

an image forming apparatus connectable to the computer mainframe, the image forming apparatus including

an image carrier for carrying a latent image,

a developer carrier for carrying a developer, and

a developer charging unit that includes a developer

15

charging member for charging the developer carried on the developer carrier and a support member for supporting the developer charging member,

wherein the developer charging member and the support member are fixed by spot welding, and the image forming

20

apparatus develops the latent image carried on the image carrier with the developer carried on the developer carrier,

wherein the support member includes a first bent portion and a second bent portion that are formed by bending a rectangular member along a longitudinal direction thereof,

25

the support portion supports the developer charging

member,

a direction in which the first bent portion is bent is opposite to a direction in which the second bent portion is bent, and

5 the developer charging unit includes a free length determining member for determining a free length of the developer charging member.

40. A heat releasing device for a developing device in a rotary development unit in which a selected one of developing devices is placed adjacent to a photosensitive body in an image forming apparatus by rotating the developing devices in a loaded state about a rotary shaft so that toner within the selected developing device is moved
15 onto the photosensitive body,

the developing device comprising:

a housing having a peripheral surface and two end faces at the both sides of the peripheral surface;

a toner container formed in the housing and containing
20 toner;

a roller for supplying the toner in the toner container onto the photosensitive body; and

a gear provided on a metal rotation shaft of the roller outside the housing for rotatively driving the roller;

25 wherein the gear has a double-layer structure

constructed by an outer part made of resin formed with gear
teeth in an outer periphery and an inner part made of
sintered metal positioned inside of the outer part, the
inner part being inserted by and fixed with the rotation
5 shaft of the roller.

41. A heat releasing device for a developing device
according to claim 40, wherein the roller for supplying
toner onto the photosensitive body is a supply roller
10 provided adjacent to the toner container and having a
rotation shaft rotatably supported by the two end faces and
a developing roller having a peripheral surface in contact
with a peripheral surface of the supply roller and a
rotation shaft rotatably supported by the two end faces.

15

42. A heat releasing device for a developing device
according to claim 41, wherein the gear in the double-layer
structure is a developing-roller driving gear for driving
the developing roller.

20

43. A heat releasing device for a developing device
according to claim 42, wherein the developing-roller driving
gear has a peripheral surface formed with first and second
gear parts different in diameter and adjacent with respect
25 to a rotation axis direction, the inner part lying astride

the first and second gear parts.

44. A heat releasing device for a developing device
according to claim 40, wherein the gear in the double-layer
5 structure is formed by insert-molding an outer part member
in a state that the inner part is present.

45. A developing device having a heat releasing device
according to claim 40.

10

46. A deformation preventing device for a developing device
in a rotary development unit in which a selected one of
developing devices is placed adjacent to a photosensitive
body in an image forming apparatus by rotating the
15 developing devices in a loaded state about a rotary shaft so
that toner within the selected developing device is moved
onto the photosensitive body, the developing device
comprising:

a housing having a peripheral surface and two end faces
20 at the both sides of the peripheral surface;

a toner container formed in the housing and containing
toner;

a supply roller provided adjacent to the toner
container and having a rotation shaft rotatably supported by
25 the two end faces;

a developing roller having a peripheral surface in contact with the peripheral surface of the supply roller and having a rotation shaft rotatably supported by the two end faces;

5 a developing-roller driving gear provided at one end of the rotation shaft of the developing roller and having a first gear part formed with helical teeth on a peripheral surface thereof; and

10 an intermediate gear provided on a same side as the first gear part of the developing-roller driving gear, and having a rotation shaft supported by the end faces of the housing, and a peripheral surface formed with helical teeth in mesh with the first gear, for receiving a drive force from a driving source;

15 the helical teeth on the first gear of the developing-roller driving gear and the helical teeth on the intermediate gear being formed in a direction to urge the developing roller toward the first gear;

20 wherein the deformation preventing device is provided in a state restricted in axial movement on the support shaft of the intermediate gear, and

the deformation preventing device is in abutment against an end outer face of the housing on a side the intermediate gear is provided.

25

47. A deformation preventing device for a developing device in a rotary development unit in which a selected one of developing devices is placed adjacent to a photosensitive body in an image forming apparatus by rotating the

5 developing devices in a loaded state about a rotary shaft so that toner within the selected developing device is moved onto the photosensitive body, the developing device comprising:

10 a housing having a peripheral surface and two end faces at the both sides of the peripheral surface;

a toner container formed in the housing and containing toner;

15 a supply roller provided adjacent to the toner container and having a rotation shaft rotatably supported by the two end faces;

a developing roller having a peripheral surface in contact with the peripheral surface of the supply roller and having a rotation shaft rotatably supported by the two end faces;

20 a supply-roller driving gear provided at one end of the rotation shaft of the developing roller and formed with spur teeth on a peripheral surface thereof;

a developing-roller driving part provided at one end of the rotation shaft of the developing roller and having a
25 second gear part formed on a peripheral surface with spur

teeth in mesh with the supply-roller driving gear and a first gear part provided adjacent to the second gear part and formed with helical teeth on a peripheral surface thereof; and

5 an intermediate gear provided on a same side as the first gear part of the developing-roller driving gear and having a rotation shaft supported by the end faces of the housing, and a peripheral surface formed with helical teeth in mesh with the first gear, for receiving a drive force
10 from a driving source;

 the helical teeth on the first gear of the developing-roller driving gear and the helical teeth on the intermediate gear being formed in a direction to urge the developing roller toward the first gear;

15 wherein the deformation preventing device is provided in a state restricted in axial movement on the support shaft of the intermediate gear, and

 the deformation preventing device is in abutment against an end outer face of the housing on a side the
20 intermediate gear is provided.

48. A deformation preventing device of a developing device according to claim 46, wherein the intermediate gear is rotatable about the support shaft of the intermediate gear,
25 the deformation preventing device having a pressure

dispersing plate placed in abutment against an outer surface of the housing at an area sufficiently broader than a section of the support shaft of the intermediate gear.

- 5 49. A deformation preventing device of a developing device according to claim 48, wherein the support shaft of the intermediate gear is fixed with a holding part, by the holding part the pressure dispersing plate being urged on the end outer face of the housing.

10

50. A deformation preventing device for a developing device according to claim 48, wherein the pressure dispersing plate is a metal plate.

- 15 51. A developing device having a deformation preventing device according to claim 46.

52. An image forming apparatus using a developing device according to claim 51.

20

53. A frictional-heat-generation suppressing device for a developing device in a rotary development unit in which a selected one of developing devices is placed adjacent to a photosensitive body in an image forming apparatus by

- 25 rotating the developing devices in a loaded state about a

rotary shaft so that toner within the selected developing device is moved onto the photosensitive body, the developing device comprising:

a housing formed therein with a toner container;

5 a developing roller having a rotation shaft rotatably supporting by end faces of the housing;

an urging device for urging the developing roller toward one of the end faces of the housing;

10 an end abutment part formed in an inner surface of the housing, to restrict from moving the end face of the developing roller positioned on a side in a direction the developing roller is urged; and

15 a low friction member provided in a manner sandwiched between the end face of the developing roller and the end abutment part.

54. A frictional-heat-generation suppressing device for a developing device in a rotary development unit in which a selected one of developing devices is placed adjacent to a
20 photosensitive body in an image forming apparatus by rotating the developing devices in a loaded state about a rotary shaft so that toner within the selected developing device is moved onto the photosensitive body, the developing device comprising:

25 a housing formed therein with a toner container;

a supply roller provided adjacent to the toner container and having a rotation shaft rotatably supported by end faces of the housing;

5 a developing roller having a peripheral surface in contact with a peripheral surface of the supply roller and a rotation shaft rotatably supported by the end faces of the housing;

an urging device for urging the developing roller on one of the end faces of the housing;

10 an end abutment part formed in an inner surface of the housing, to restrict from moving the end face of the developing roller positioned on a side in a direction the developing roller is urged; and

a low friction member provided in a manner sandwiched
15 between the end face of the developing roller and the end abutment part.

55. A frictional-heat-generation suppressing according to claim 53, wherein the low friction member is a polyslider.

20

56. A frictional-heat-generation suppressing according to claim 53, wherein the urging device is structured by a developing-roller driving gear provided at one end of the rotation shaft of the developing roller and formed with
25 helical teeth in a peripheral surface thereof, and an

intermediate gear having a support shaft supported by the end faces of the housing and formed in a peripheral surface with helical teeth in mesh with the developing-roller driving gear, and

5 the developing roller is urged toward the developing-roller driving gear by an action of the helical teeth.

57. A developing device having a frictional-heat-generation suppressing device according to claim 53.

10

58. An image forming apparatus using a developing device according to claim 57.

59. An electric-contact urging device for an electric
15 contact comprising:

 a conductor elastic plate having an electric contact for contact with an end of a rotation shaft is fixed on a fixing member positioned around the end of the rotation shaft at first and second fixing parts, the electric contact
20 with the end of the rotary shaft being positioned between the first and second fixing parts,

 wherein the conductor elastic plate has a first arm part extending between the first fixing part and the electric contact and a second arm part extending between the
25 second fixing part and the electric contact,

the first arm part and the second arm part intersect at an intersecting angle of 30 to 150 degree, and

the electric contact is elastically urged on and contacted with an end of the rotation shaft by an elasticity
5 of the conductor elastic plate.

60. An electric-contact urging device on a rotation shaft according to claim 59, wherein the intersecting angle is approximately 90 degrees.

10

61. An electric-contact urging device on a rotation shaft according to claim 59, wherein the first and second fixing parts are fixed by screws.

15 62. An electric-contact urging device on a rotation shaft according to claim 59, wherein the rotation shaft is a rotation shaft of a roller for toner carriage provided in a developing device capable of moving toner to a photosensitive body by positioning adjacent to the

20 photosensitive body of an image forming apparatus, and

the electric contact is to be used as an electricity feed base point for charging an outer peripheral surface of the roller.

25 63. An electric-contact urging device on a rotation shaft

comprising:

a conductor elastic plate having an electric contact
for contact with one end of a rotation shaft that is fixed
to a fixing member positioned around the end of the rotation
5 shaft, at one fixing part;

the electric contact being formed close to a free end
of a branch arm part branched from an intermediate of a
third arm part extending from the one fixing part;

a fourth arm part bent approximately 90 degrees at an
10 opposite end of the third arm part to the one fixing part
and extending toward the other end of the rotation shaft;

the fourth arm part being formed with another fixing
part for fixing the third arm part to the fixing member in a
state of pulling toward the other end of the rotation shaft;

15 wherein the electric contact is elastically urged by
and contacted with one end of the rotation shaft by an
elasticity of the conductor elastic plate.

64. An electric-contact urging device on a rotation shaft
20 according to claim 63, wherein the one fixing part and the
other fixing part are fixed by screws.

65. An electric-contact urging device on a rotation shaft
according to claim 63, wherein the rotation shaft is a
25 rotation shaft of a roller for toner carriage provided in a

developing device for transferring toner to a photosensitive body by being placed adjacent to the photosensitive body of an image forming apparatus, the electric contact being to be used as an electricity feed base point for charging an outer
5 peripheral surface of the roller.

66. An electric-contact urging device on a rotation shaft wherein an electric-contact urging device according to claim 59 is provided on one conductor elastic plate.

10

67. A developing device having an electric-contact urging device on a rotation shaft according to claim 59.

68. A seal structure of a developing device comprising:
15 a developing roller;
a toner layer regulation member which is brought into contact with the developing roller; and
seal members which are provided at both ends of the developing roller,

20

wherein hard resin adhesive is filled in a gap between said toner layer regulation member and the seal member.

69. The seal structure of developing device according to Claim 68, wherein said toner layer regulation member
25 comprises a leaf spring and a regulation blade, and

the hard resin adhesive is filled in a gap between the leaf spring and the seal member.

70. The seal structure of developing device according to
5 Claim 69, wherein the hard resin adhesive is filled in a gap between the regulation blade and the seal member.

71. The seal structure of developing device according to
Claim 68, wherein said hard resin adhesive is UV-curing
10 adhesive.

72. A developing device comprising:
a developing roller having a rotation shaft formed on both sides in an axial direction of the roller body; and
15 a distance keeping member which is rotatably attached to said rotation shaft and comes into contact with a photosensitive body thereby to keep the distance between the roller body and the photosensitive body,
wherein lubricant is filled between said distance
20 keeping member and the rotation shaft.

73. The developing device according to Claim 72, wherein said lubricant is silicon oil or grease.

25 74. The developing device according to Claim 72, wherein a

lubricant absorber is interposed between said distance
keeping member and the side surface of the roller body.

75. The developing device according to Claim 74, wherein a
5 high sliding resin plate is arranged between said distance
keeping member and the lubricant absorber.